

# 1x2(2x2) Single Mode C/L Band Broadband Tap



## Product Features

- Moisture-Resistant
- Impact-Resistant
- Vibration-Resistant
- Compact Size

## Product Applications

- Submarine Cable System
- Submarine Optical Amplifier
- Optical Communication System
- EDFA Module

## Specifications

Parameter	Unit	Premium	A grade
Port Configuration		1x2 or 2x2	
Bandwidth	nm	C Band (1528-1565) or L Band (1570-1605)	
Excess Loss	Typ. dB	0.07	0.1
PDL	Max. dB	0.1	0.15
Return Loss*	Min. dB	50	45
Operating power	Max. W	5	
Operating Temperature	°C	-40 to +85	
Storage Temperature	°C	-50 to +85	
Package Type	mm	S6	Ø3x54: for bare fiber

\* >60dB on request for 1x2 structure.

Test at central wavelength only.

## Ultra-High Reliability Test

## Results

High Temperature Storage (85°C)	6,000 hours
Temperature Cycling (-40°C to 85°C)	1,000 cycles
Damp Heat Test (85°C /85%RH)	5,000 hours
Low Temperature Storage (-40°C)	6,000 hours
Impact Test (1000g, 1ms)	8 times/each axes (3 axes)
Vibration Test (10 to 2,000 Hz/20g)	20 minutes/12 times (3 axes)

## Splitting Ratio & Insertion Loss Conversion Table

Splitting Ratio	Maximum Insertion Loss(dB)			
	Premium		A grade	
	Output Port 1	Output Port 2	Output Port 1	Output Port 2
95:5	0.4	14.6	0.5	18.4
96:4	0.3	16.0	0.4	19.0
97:3	0.3	17.5	0.4	19.5
98:2	0.2	19.0	0.3	20.0
99:1	0.2	21.5	0.3	22.0

## Ordering Information

H	R	B	S								
				Wavelength	Structure	Splitting Ratio	Grade	Package	Fiber Type	Pigtail	Fiber Length
				C=C Band L=L Band	1=1x2 2=2x2	99=99:1 96=96:2 97=97:3 96=96:4 95=95:5	P=Premium A=A grade	5=S6	1=SMF-28e	S=250um bare fiber	0=0.5m 1=0.75m 2=1.0m S=Specify

Note: 1. Central Wavelength can be customized for different applications.  
2. All specifications are subject to change without notice.