

3x3 Polarization-Insensitive Fused PM Fiber Splitter (Mixer)



Product Features

- Operating on both Fast and Slow Axis
- Low Excess Loss
- Polarization-Insensitive
- High Power Handling
- Telcordia GR-1221 Compliant Test

Product Applications

- Optical Amplifier
- Optical Sensor
- Coherent Optical System
- Optical Testing Equipment

| Specifications | | | Splitting Ratio: 33:33:33 | |
|-------------------------------|------|----|----------------------------------|---------|
| Parameter | Unit | | Premium | A grade |
| Port Configuration | | | 3x3 | |
| Central Wavelength | nm | | 1310, 1480, 1550, 2000 | |
| Bandwidth | nm | | ±20 | |
| Excess Loss | Typ. | dB | 0.7 | 0.9 |
| Excess Loss | Max. | dB | 0.9 | 1.1 |
| Polarization Dependent Loss | Max. | dB | 0.1 | 0.2 |
| Polarization Extinction Ratio | Min. | dB | 17 | 15 |
| Splitting Ratio Tolerance | Max. | % | ±10 | ±13 |
| Return Loss* | Min. | dB | 50 | 45 |
| Directivity* | Min. | dB | 55 | |
| Operating power | Max. | W | 2 | |
| Operating Temperature | | °C | -40 to +85 | |
| Storage Temperature | | °C | -50 to +85 | |
| Package Type | | mm | S6 / S12 / M2 | |

Above PER is for more than 10%(CR) port, it's 2dB lower for no more than 10%(CR) port, and 4dB lower for no more than 5%(CR) port.

All specifications are before connectors. PER is 2dB lower and EL is 0.2dB higher after connectors.

* Test at central wavelength only.

Ordering Information

| | | | | | | | | | | |
|---|-----------|-----------------|------------------------|---|---------------|--|---|--|--|--|
| P | I | B | S | | | | | | | |
| | | | | 3 | 3 | | | | | |
| Wavelength | Structure | Splitting Ratio | Grade | Package | Fiber Type | Fiber Length | Connector | | | |
| 4=1550nm 5=1480nm 7=1310nm P=2000nm S=Specify | A=3x3 | 33=33:33:33 | P=Premium A=A grade | 5=S6 with 250um bare fiber pigtail B=S12 with 0.9mm loose tube E=M2 with 3mm cable | E=Panda fiber | 0=0.5m 1=0.75m 2=1.0m S=Specify | 0=None 1=FC/PC 2=FC/SPC 3=FC/APC 7=FC/UPC | | | |

Note: 1. Central Wavelength can be customized for different applications.
2. All specifications are subject to change without notice.